

Datum: 21.05.2025



(slika je simbolična)

Filter-regulator z PC zbir.Vel.1,G 3/8, 0.5 - 10 bar

Kategorija: [Combined service unit, PC bowl, manual drain](#)Šifra: **101090RIE**

Kratek opis

Combi-service unit with PC container, manual bleeder valve, Size 1, G 3/8, Input pressure max. 16 bar, Control range 0.5 - 10 bar

A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design.

The pressure setting can be locked by pushing the knob down.

Oil can be filled under pressure.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Manual drain valve
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Tesnilo	NBR
Vidna kupola	PA
Vzmet pokrova motorja	PA
Min. krmilno območje [bar]	0.5
Velikost	1
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Rang filtra [μ m]	40
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	67.0
C [mm]	68.5
B [mm]	217.0
Pretok [l/min]	1400