

Datum: 02.05.2025

Davčna št.: SI 56119488

Telefon: 01 500 14 42

E-mail: info@podjetje-trg.si

WWW: www.mail.karchertest.staging.digitalist.si



(slika je simbolična)

Filter umazan. nikljana med., G 1, DN 25, šrina mrežice 0.5 mm

Kategorija: [Dirt strainer nickel-plated brass, mesh width 0.5](#)

Šifra: **140997RIE**

Kratek opis

Dirt strainer, nickel-plated brass, Sieve insert mesh width 0.5 mm, Operating temp. -20 °C to 110 °C, G 1, DN 25, PN max. 20 bar
Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Glava	Nickel-plated brass
Navoj	G 1
Ohišje	Nickel-plated brass
Standardni navoj	G thread acc. to ISO 228-1, tolerance class B
Tesnilo	NBR O-ring
Zaslon	Stainless steel
Velikost mrežice [mm]	0.5
Max. obratovalni tlak [bar]	20
DN	25
a/f 2 [mm]	32
a/f 1 [mm]	38
C [mm]	56.0
L [mm]	87.0
Max. delovna temperatura [°C]	110