

Datum: 30.04.2025



(slika je simbolična)

Filter z aktivnim ogljem »FUTURA-mali« Kov. pos. Vel.0,G1/4

Kategorija: [Activated carbon filter with metal bowl](#)

Šifra: **142454RIE**

Kratek opis

Active charcoal filter »FUTURA-mini«, Metal container, 0.005 mg/m³, Size 0, G 1/4, Input pressure 0 - 12 bar, Temp. -10°C to 50°C

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.

Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P ₂ = 6 bar and pressure drop Δ _p = 0.2 bar
Merjenje pretoka	G 1/4
Navoj	PA66 GF60
Ohišje	Metal container
Posoda	Plastic
Priključni navoj	FUTURA-mini
Serijska	Compressed air, neutral gases
Srednje	NBR
Tesnilo	0.005
Vsebnost olja v ostanku [mg/m ³]	12
Max. vhodni tlak [bar]	27.0
C [mm]	43.0
A [mm]	50
Max. temperaturno območje [°C]	114.0
B [mm]	470
Pretok [l/min]	