

Datum: 01.05.2025



(slika je simbolična)

Filter z aktivnim ogljem »FUTURA« z PC zbiralnik, Velikost 4, G 1

Kategorija: [Activated carbon filter, PC bowl, bowl guard](#)

Šifra: **100196RIE**

Kratek opis

Active charcoal filter »FUTURA« with PC container and protective cage, 0.005 mg/m³, Size 4, G 1, Input pressure 0 - 16 bar

Activated carbon filters in modern design for compliance with strict compressed air purity requirements.

Activated carbon filters are used to absorb oil vapour up to a residual oil content of 0.005 mg/m³ from compressed air and gases.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Activated carbon At P ₂ = 6 bar and pressure drop Δ_p = 0.2 bar
Merjenje pretoka	G 1
Navoj	PA66 GF60
Ohišje	Polycarbonate container with protective cage
Posoda	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	4
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	58.0
A [mm]	85.0
B [mm]	242.0
Pretok [l/min]	2500