

Datum: 30.04.2025



(slika je simbolična)

Filter z aktivnim ogljem »multifix«Kov. pos.Vel.1,G 1/4

Kategorija: [Activated carbon filter with metal bowl](#)

Šifra: **100543RIE**

Kratek opis

Active charcoal filter »multifix« with metal container, 0.005 mg/m³, Size 1, G 1/4, Input pressure max. 20 bar, Temp. max. 60 °C

For filtering odours out of compressed air.

The activated carbon absorbs the oil vapour molecules contained in the compressed air.

A separate filter route prevents activated carbon particles from entering the air flow.

Tehnične Specifikacije

Element filtra	Activated carbon-POM
Merjenje pretoka	At P ₁ = 6 bar and pressure drop Δ _p = 0.2 bar
Navoj	G 1/4
Ohišje	Die-cast zinc
Posoda	Metal container
Serijska	multifix
Tesnilo	NBR
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	1
DN	6
Max. vhodni tlak [bar]	20
C [mm]	27.0
A [mm]	47.8
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	110.0
B [mm]	137.0
Pretok [l/min]	380