

Datum: 02.05.2025



(slika je simbolična)

[Filter z aktivnim ogljem »multifix-mali«, Kovinska posoda, G 1/8](#)

Kategorija: [Activated carbon filter with metal bowl](#)
Šifra: **100378RIE**

Kratek opis

Active charcoal filter »multifix-mini«, metal container, 0.005 mg/m³, G 1/8, Input press. max. 16 bar, Med./ambient temp. max.60°C

For filtering odours out of compressed air.

The activated carbon absorbs the oil vapour molecules contained in the compressed air.

A separate filter route prevents activated carbon particles from entering the air flow.

Tehnične Specifikacije

Element filtra	Activated carbon-POM
Merjenje pretoka	At P ₁ = 6 bar and pressure drop Δ _p = 0.2 bar
Navoj	G 1/8
Ohišje	Die-cast zinc
Posoda	Metal container
Serija	multifix-mini
Tesnilo	NBR
Vsebnost olja v ostanku [mg/m ³]	0.005
DN	5
C [mm]	12.3
Max. vhodni tlak [bar]	16
A [mm]	40.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	85.0
B [mm]	97.3
Pretok [l/min]	310