

Datum: 09.05.2025



(slika je simbolična)

Filter z aktivnim ogljem »multifix-mali«, PC zbiralnik, G 1/8

Kategorija: [Activated carbon filter with polycarbonate bowl](#)

Šifra: **100376RIE**

Kratek opis

Active charcoal filter »multifix-mini«, PC container, 0.005 mg/m³, G 1/8, Input pressure max. 16 bar, Med./ambient temp. max. 60°C

For filtering odours out of compressed air.

The activated carbon absorbs the oil vapour molecules contained in the compressed air.

A separate filter route prevents activated carbon particles from entering the air flow.

Tehnične Specifikacije

Element filtra	Activated carbon-POM
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop $\Delta_p = 0.2$ bar
Navoj	G 1/8
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Serija	multifix-mini
Tesnilo	NBR
Vsebnost olja v ostanku [mg/m ³]	0.005
DN	5
C [mm]	12.3
Max. vhodni tlak [bar]	16
A [mm]	40.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	95.5
B [mm]	107.8
Pretok [l/min]	310