

Datum: 10.05.2025



(slika je simbolična)

Filter z aktivnim ogljem »multifix«PC zbir.Vel.4,G 3/4

Kategorija: [Activated carbon filter with PC bowl, bowl guard](#)

Šifra: **133149RIE**

Kratek opis

Active charcoal filter »multifix« with PC container and protective cage, 0.005 mg/m³, Size 4, G 3/4, Input pressure max. 16 bar

For filtering odours out of compressed air.

The activated carbon absorbs the oil vapour molecules contained in the compressed air.

A separate filter route prevents activated carbon particles from entering the air flow.

Tehnične Specifikacije

Element filtra	Activated carbon-POM
Merjenje pretoka	At P ₁ = 6 bar and pressure drop Δ _p = 0.2 bar
Navoj	G 3/4
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serijska	multifix
Tesnilo	NBR
Vsebnost olja v ostanku [mg/m ³]	0.005
Velikost	4
Max. vhodni tlak [bar]	16
DN	20
C [mm]	58.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	85.0
D [mm]	183.0
B [mm]	241.0
Pretok [l/min]	3000