

Datum: 01.05.2025



(slika je simbolična)

Filter z aktivnim ogljem z diferencialnim manometrom, G 2

Kategorija: [Activated carbon filter with diff. pressure gauge](#)

Šifra: **101583RIE**

Kratek opis

Active charcoal filter with differential pressure gauge, 0.005 mg/m³, G 2, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C
For adsorbing vaporous media.

A micro-filter must be connected upstream if dried air is not available.

Tehnične Specifikacije

Element filtra	Activated carbon
Merjenje pretoka	At $P_1 = 6$ bar and pressure drop Δp = 0.5%
Navoj	G 2
Ohišje	Aluminium
Posoda filtra	Aluminium
Vsebnost olja v ostanku [mg/m ³]	0.005
D [mm]	1.148.0
Max. označeni razpon diferencialnega manometra [bar]	2
Min. vhodni tlak [bar]	4
Min. sobna temperatura [°C]	5
Min. temperatura medija [°C]	5
Max. vhodni tlak [bar]	16
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	72.0
A [mm]	118.0
B2 [mm]	720.0
B1 [mm]	819.0
Pretok [l/min]	6650