

Datum: 30.04.2025



(slika je simbolična)

## Filter za visoke pritiske do 60 bar, 40 µm, G 1/2

Kategorija: [Filters for high pressures up to 60 bar](#)

Šifra: **101175RIE**

### Kratek opis

Filter for high pressures up to 60 bar, with manual bleeder valve, 40 µm, G 1/2, Brass container, Operating temp. 0 °C to 90 °C

Centrifugal separator with a sintered filter element.

### Tehnične Specifikacije

|                               |                                                         |
|-------------------------------|---------------------------------------------------------|
| Merjenje pretoka              | At $P_2 = 6$ bar and pressure drop $\Delta p = 0.5$ bar |
| Navoj                         | G 1/2                                                   |
| Odtok kondenzata              | Manual drain valve                                      |
| Ohišje                        | Aluminium                                               |
| Posoda                        | Brass                                                   |
| Tesnilo                       | NBR                                                     |
| C [mm]                        | 25.0                                                    |
| Rang filtra [µm]              | 40                                                      |
| Max. vhodni tlak [bar]        | 60                                                      |
| A [mm]                        | 65.0                                                    |
| Max. delovna temperatura [°C] | 90                                                      |
| B [mm]                        | 187.0                                                   |
| Pretok [l/min]                | 2660                                                    |