

Datum: 02.05.2025



(slika je simbolična)

## **GEKA Zaščitne hitre spojke za vrtno cevi z N.N.Med.G 1 o.**

Kategorija: [GEKA threaded piece, ET, rigid, safety version](#)

Šifra: **107795RIE**

### **Kratek opis**

GEKA threaded piece, rigid, Safety design, bright brass, G 1 o., Operating pressure max. 40 bar, Med./ambient temp. -10°C to 90°C

Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc.

Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

### **Tehnične Specifikacije**

|                              |        |
|------------------------------|--------|
| Min. sobna temperatura [°C]  | -10    |
| Min. temperatura medija [°C] | -10    |
| Povezava                     | G 1 ET |
| Tesnilo                      | NBR    |
| Max. obratovalni tlak [bar]  | 40     |
| Max. sobna temperatura [°C]  | 90     |
| Max. temperatura medija [°C] | 90     |