

Datum: 30.04.2025



(slika je simbolična)

Glicerinski man.ekscent. priklop zadaj G 1/2, 0-40 bar, Ø100

Kategorija: [Glycerine pressure gauge, connection rear](#)

Šifra: **102239RIE**

Kratek opis

Glycerine pressure gauge with metal housing, Connection, rear, eccentric, G 1/2, Goods class 1.0, Measurement range 0-40 bar, Ø100

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy,

do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Hot-pressed brass
Položaj povezave	rear, excentrical
Povezava	G 1/2
Prednje steklo	Plexiglass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Stisnjen okvir	CrNi steel
Razred točnosti	1.0
Stopnja rasti na območju skale - bar [bar]	1
Merilno območje max. bar	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premier [mm]	100
Vrsta	213.40