

Datum: 30.04.2025



(slika je simbolična)

## Glicerinski manometer, CrNi jeklo, G 1/2, 0 - 2.5 bar, Ø 100

Kategorija: [Glycerine pressure gauges, CrNi steel - 233.30](#)

Šifra: **102393RIE**

### Kratek opis

Glycerine pressure gauge, CrNi steel safety design,  
Connection radial bottom, G 1/2, Measurement range 0 - 2.5  
bar, Ø 100

Glycerine-filled bourdon-tube pressure gauge, CrNi steel  
type, with solid baffle wall and blow-out (safety housing).  
Suitable for gaseous or liquid, corrosive and crystallising  
media which do not have high viscosity, also in corrosive  
atmosphere.

### Tehnične Specifikacije

|                                               |                           |
|-----------------------------------------------|---------------------------|
| Min. sobna temperatura [°C]                   | -20                       |
| Min. temperatura medija [°C]                  | -20                       |
| Material                                      | CrNi steel                |
| Material Prozessanschluss                     | CrNi steel                |
| Položaj povezave                              | radial on bottom          |
| Povezava                                      | G 1/2                     |
| Prednje steklo                                | Laminated safety<br>glass |
| Spodnja/Zgornja meja območja                  | Positive pressure         |
| Stopnja rasti na območju skale -<br>bar [bar] | 0.05                      |
| Razred točnosti                               | 1.0                       |
| Merilno območje max. bar                      | 2.5                       |
| Max. sobna temperatura [°C]                   | 60                        |
| Max. temperatura medija [°C]                  | 100                       |
| Premer [mm]                                   | 100                       |
| Vrsta                                         | 233.30                    |