

Datum: 30.04.2025



## Glicerinski manometer »pressure line« G 1/4, 0-60 bar/850 psi

(slika je simbolična)

Kategorija: [Glycerine pressure gauge, connection on rear](#)

Šifra: **116332RIE**

### Kratek opis

Glycerine press. gauge »pressure line« Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0-60 bar/850 psi, Ø 63

Low-priced series of high-quality, glycerine-filled pressure gauges with stainless steel housing for all applications involving measurements in areas with high dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                                                    |
|--------------------------------------------|----------------------------------------------------|
| Min. sobna temperatura [°C]                | -20                                                |
| Min. temperatura medija [°C]               | -20                                                |
| Material Prozessanschluss                  | Copper alloy                                       |
| Merilni element                            | Brass                                              |
| Ohišje                                     | Stainless steel                                    |
| Položaj povezave                           | rear, central                                      |
| Povezava                                   | G 1/4                                              |
| Prednje steklo                             | Glass                                              |
| Premikanje                                 | Brass                                              |
| Različica                                  | Bourdon-tube pressure gauge with glycerine filling |
| Razred točnosti                            | 1.6                                                |
| Stopnja rasti na območju skale - bar [bar] | 2                                                  |
| Max. sobna temperatura [°C]                | 60                                                 |
| Max. temperatura medija [°C]               | 60                                                 |
| Merilno območje max. bar                   | 60                                                 |
| Premier [mm]                               | 63                                                 |