

Datum: 08.05.2025



(slika je simbolična)

Glicerinski manometer, priklop spodaj, G 1/2, 0-100 bar, Ø 100

Kategorija: [Glycerine pressure gauge, conn. radial on bottom](#)

Šifra: **102201RIE**

Kratek opis

Glycerine pressure gauge with metal housing, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range 0-100 bar, Ø 100

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy,

do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	CrNi steel 1.4571
Ohišje	Hot-pressed brass
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Plexiglass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Stisnjen okvir	CrNi steel
Razred točnosti	1.0
Stopnja rasti na območju skale - bar [bar]	2
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Merilno območje max. bar	100
Premier [mm]	100
Vrsta	213.40