

Datum: 11.05.2025



(slika je simbolična)

## Glicerinski manometer, priklop spodaj, G 1/4, 0 - 250 bar, Ø 63

Kategorija: [Glycerine pressure gauge, conn. radial on bottom](#)

Šifra: **102086RIE**

### Kratek opis

Glycerine pressure gauge, plastic housing, Connection radial bottom, G 1/4, Goods class 2.5, Measurement range 0 - 250 bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy,

do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                                            |
|--------------------------------------------|--------------------------------------------|
| Min. sobna temperatura [°C]                | -20                                        |
| Min. temperatura medija [°C]               | -20                                        |
| Material Prozessanschluss                  | Copper alloy                               |
| Merilni element                            | Copper alloy                               |
| Ohišje                                     | Plastic, black (with panel-mounting bezel) |
| Položaj povezave                           | radial on bottom                           |
| Povezava                                   | G 1/4                                      |
| Prednje steklo                             | PMMA, welded to housing                    |
| Premikanje                                 | Copper alloy                               |
| Spodnja/Zgornja meja območja               | Positive pressure                          |
| Razred točnosti                            | 2.5                                        |
| Merilno območje max. psi                   | 3.600                                      |
| Stopnja rasti na območju skale - bar [bar] | 10                                         |
| Max. sobna temperatura [°C]                | 60                                         |
| Max. temperatura medija [°C]               | 60                                         |
| Premier [mm]                               | 63                                         |
| Vrsta                                      | 113.13                                     |
| Merilno območje max. bar                   | 250                                        |