

Datum: 09.05.2025



Glicerinski manometer, priklop spodaj, G 1/4, -1 / +9 bar, Ø 63

(slika je simbolična)

Kategorija: [Glycerine pressure gauge, conn. radial on bottom](#)

Šifra: **102165RIE**

Kratek opis

Glycerine pressure gauge with metal housing, Connection radial bottom, G 1/4, Goods class 1.6, Measurement range -1 / +9 bar, Ø 63

Glycerine-filled bourdon-tube pressure gauge.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy,

do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Merilno območje min. bar	-1
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Hot-pressed brass
Položaj povezave	radial on bottom
Povezava	G 1/4
Prednje steklo	Plexiglass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Vacuum/Positive pressure
Stisnjen okvir	CrNi steel
Stopnja rasti na območju skale - bar [bar]	0.5
Razred točnosti	1.6
Merilno območje max. bar	9
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premier [mm]	63
Vrsta	213.40