

Datum: 01.05.2025



Glicerinski manometer, sprednji obroč, G 1/4, -1 / 0 bar, Ø 63

(slika je simbolična)

Kategorija: [Glycerine pressure gauges, hot-pressed brass house](#)

Šifra: **102246RIE**

Kratek opis

Glycerine pressure gauge, front ring, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range -1 / 0 bar, Ø 63

Bourdon-tube pressure gauge in standard design, with panel-mounting bezel

made of chrome-plated and polished steel.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy,

do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Merilno območje min. bar	-1
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Hot-pressed brass
Položaj povezave	rear, central
Povezava	G 1/4
Prednje steklo	Plexiglass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Vacuum
Stopnja rasti na območju skale - bar [bar]	0.05
Razred točnosti	1.6
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premier [mm]	63
Vrsta	213.40