

Datum: 01.05.2025



(slika je simbolična)

Glicerinski manometer, trikoten sprednji obroč, G 1/2, -1 / 0 bar

Kategorija: [Glycerine pressure gauges with clamp fixing](#)

Šifra: **102293RIE**

Kratek opis

Glycerine pressure gauge, bracket fastening, triangle front ring, Connection, rear, eccentric, G 1/2, Meas. range -1 / 0 bar, Ø100

Bourdon-tube pressure gauge in standard design, with clamp fixing.

For measurements in areas with high, dynamic pressure loads and vibration levels.

Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Merilno območje min. bar	-1
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Hot-pressed brass
Položaj povezave	rear, excentrical
Povezava	G 1/2
Prednje steklo	Plexiglass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Vacuum
Stopnja rasti na območju skale - bar [bar]	0.02
Razred točnosti	1.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premier [mm]	100
Vrsta	213.40