

Datum: 30.04.2025



(slika je simbolična)

Hidravlična spojka, Serija B, , G 3/4 notranji navoj, I.D. 19

Kategorija: [Hydraulic couplings, female](#)

Šifra: **107731RIE**

Kratek opis

Hydraulic coupling, Series B, Steel, G 3/4 IT, I.D. 19,
Operating pressure max. 300 bar, Operating temp. -30 °C to
100 °C

Acc. to ISO 7241-1, B Series.

This coupling series combines an extremely small pressure
drop with maximum hydraulic power transmission.

Interchangeable with all couplings and plugs manufactured
according to the above standard.

The patented pressure eliminator permits disconnection
even if back pressure has built up (up to 200 bar).

The pressure eliminator can be used in all applications
where there is a risk of pressure build-up after the line has
been separated. It allows effortless connection under
pressure.

The mating part must be pressureless in order for the
eliminator to function optimally.

Areas of application: chemical industry, food technology,
automotive, offshore.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-30
Krogla	Stainless steel
Ohišje	Steel
Potisni čep	Steel
Povezava	G 3/4 IT
Sprostitutveni rokav	Steel
Tesnilo	NBR
Ventil	Brass
Vzmet	Stainless steel
DN	19
a/f [mm]	46
Volumski pretok (olje) [l/min]	75
Dolžina [mm]	81.0
Max. delovna temperatura [°C]	100
Max. obratovalni tlak [bar]	300