

Datum: 03.05.2025



(slika je simbolična)

Hidravlična spojka Serija A.I.D. 13, Med.G 1/2 N.N.

Kategorija: [Hydraulic coupling, female](#)

Šifra: **107723RIE**

Kratek opis

Hydraulic coupling, Series A, I.D. 13, Brass, G 1/2 IT,
Operating pressure max. 250 bar, Operating temp. -30 °C to
100 °C

Acc. to ISO 7241-1, A Series.

This coupling series combines an extremely small pressure
drop with maximum hydraulic power transmission.

Interchangeable with all couplings and plugs manufactured
according to the above standard.

The patented pressure eliminator permits disconnection
even if back pressure has built up (up to 200 bar).

The pressure eliminator can be used in all applications
where there is a risk of pressure build-up after the line has
been separated. It allows effortless connection under
pressure.

The mating part must be pressureless in order for the
eliminator to function optimally.

Areas of application: Agricultural machines, construction
machines, municipal engineering, transportation
engineering, industrial plant.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-30
Krogla	Stainless steel
Ohišje	Brass
Povezava	G 1/2 IT
Sprostitutveni rokav	Nickel-plated brass
Tesnilo	NBR
Ventil	Hard drawn brass
Vzmet	Stainless steel
a/f [mm]	27
Volumski pretok (olja) [l/min]	30
Dolžina [mm]	63.0
Max. delovna temperatura [°C]	100
Max. obratovalni tlak [bar]	250