

Datum: 30.04.2025



(slika je simbolična)

## Hitre spojke I.D. 10, /poniklanaMedenina, R 3/4 zunanji navoj

Kategorija: [Quick disconnect coupling DN 10, male](#)

Šifra: **141555RIE**

### Kratek opis

Quick-connect coupling I.D. 10, Steel / nickel-plated brass, R 3/4 ET, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"  
Single-sided blocking and robust quick connect coupling with high flow performance.

To prevent injuries or a ""whiplash"" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, Machine and plant engineering, Measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive, food technology, aerospace.

"

### Tehnične Specifikacije

|                              |                                   |
|------------------------------|-----------------------------------|
| Min. sobna temperatura [°C]  | -20                               |
| Min. temperatura medija [°C] | -20                               |
| Delovni tlak                 | 0 - 35 bar                        |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar |
| Navojni kos                  | Nickel-plated brass               |
| Ohišje                       | Nickel-plated brass               |
| Povezava                     | R 3/4 ET                          |
| Rokav                        | Galvanised steel                  |
| Tesnilo                      | NBR                               |
| Ventil                       | Nickel-plated brass               |
| Vzmet                        | Stainless steel                   |
| DN                           | 10                                |
| a/f [mm]                     | 27                                |
| Dolžina [mm]                 | 65.0                              |
| Max. sobna temperatura [°C]  | 100                               |
| Max. temperatura medija [°C] | 100                               |
| Pretok                       | 3500 l/min (air)                  |