

Datum: 30.04.2025



(slika je simbolična)

Hitre spojke I.D. 2.7, ponikljana medenina, cev 4x3

Kategorija: [Quick disconnect coupling DN 2.7, hose connector](#)

Šifra: **107093RIE**

Kratek opis

Quick-connect coupling I.D. 2.7, nickel-plated brass, Hose connection 4x3, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"
One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive.

"

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	Hose connection 4x3
Pritrdilni obroč	Stainless steel
Rokav	Nickel-plated brass
Telo ventila	Nickel-plated brass
Tesnilo	NBR
Vzmet	Stainless steel
DN	2.7
Dolžina [mm]	34.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	165 l/min (air)