

Datum: 18.05.2025



(slika je simbolična)

Hitre spojke I.D. 2.7ponikljana medenina, push-in 4 mm

Kategorija: [Quick disconnect coupling DN 2.7, push-in fitting](#)Šifra: **107096RIE**

Kratek opis

Quick-connect coupling I.D. 2.7 nickel-plated brass, push-in connection 4 mm, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C

One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Pritrdilni obroč	Stainless steel
Rokav	Nickel-plated brass
Telo ventila	Nickel-plated brass
Tesnilo	NBR
Vzmet	Stainless steel
DN	2.7
Povezava a/f [mm]	4 mm
Dolžina [mm]	10
Max. sobna temperatura [°C]	35.0
Max. temperatura medija [°C]	100
Pretok	100
	165 l/min (air)