

Datum: 09.05.2025



(slika je simbolična)

Hitre spojke I.D. 5, ponikljana medenina, cev I.D. 6

Kategorija: [Quick disconnect coupling DN 5, with hose stem](#)

Šifra: **107166RIE**

Kratek opis

Quick-connect coupling I.D. 5, nickel-plated brass, Sleeve I.D. 6, Operating pressure 0-35 bar, Med./ambient temp. -20°C to 100°C

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Krogla	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	I.D. 6
Pritrdilni obroč	Stainless steel
Rokav	Nickel-plated brass
Telo ventila	Nickel-plated brass
Tesnilo	NBR
Vzmet	Stainless steel
DN	5
Dolžina [mm]	46.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	560 l/min (air)