

Datum: 01.05.2025



(slika je simbolična)

## Hitre spojke I.D. 7.2, cev 13 mm, vrteče

Kategorija: [Quick disconnect coupling DN 7.2, swivel type](#)

Šifra: **107299RIE**

### Kratek opis

Quick-connect coupling I.D. 7.2, nickel-plated brass, Sleeve 13 mm rotating, Operating pressure 0 - 35 bar, Temp. 0 °C to 70 °C

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

### Tehnične Specifikacije

|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Delovni tlak                 | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar                            |
| Ohišje                       | Nickel-plated brass                                          |
| Povezava                     | Stem 13 mm, swivel type                                      |
| Pritrdilni obroč             | Stainless steel 1.4310                                       |
| Rokav                        | Nickel-plated brass                                          |
| Telo ventila                 | Brass with a bare metal surface                              |
| Tesnilo                      | NBR                                                          |
| Vzmet                        | Stainless steel 1.4310                                       |
| Zaporni zatič                | Stainless steel 1.4034                                       |
| DN                           | 7.2                                                          |
| Max. sobna temperatura [°C]  | 70                                                           |
| Max. temperatura medija [°C] | 70                                                           |
| Dolžina [mm]                 | 74.0                                                         |
| Pretok                       | 1000 l/min (air)                                             |