

Datum: 03.05.2025



(slika je simbolična)

Hitre spojke I.D. 7.2, Nerjavno jeklo 1.4305, G 1/4 notranji navoj

Kategorija: [Quick disconnect coupling DN 7.2, female](#)
Šifra: **107337RIE**

Kratek opis

Quick-connect coupling I.D. 7.2, Stainless steel 1.4305, G 1/4 IT, Operating pressure max. 35 bar, Temp. -25 °C to 200 °C

Classic standard coupling type, one side sealing, made of stainless steel.

The closed sleeve protects the coupling from dirt.

We recommend the use of stainless steel plugs and stems!

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, chemical / pharmaceutical industry, workshops, automotive, offshore.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-25
Min. temperatura medija [°C]	-25
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Stainless steel 1.4305
Povezava	G 1/4 IT
Pritrdilni obroč	Stainless steel 1.4310
Rokav	Stainless steel 1.4305
Telo ventila	Stainless steel 1.4305
Tesnilo	FKM
Vzmet	Stainless steel 1.4310
Zaporni zatič	Stainless steel 1.4401
DN	7.2
a/f [mm]	22
Max. obratovalni tlak [bar]	35
Dolžina [mm]	43.0
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200
Pretok	1000 l/min (air)