

Datum: 30.04.2025



(slika je simbolična)

## Hitre spojke I.D. 7.6, pocinkano /medenina,Fi cevi I.D. 8

Kategorija: [Quick disconnect coupling DN 7.6, with hose stem](#)

Šifra: **107363RIE**

### Kratek opis

Quick-connect coupling I.D. 7.6, galvanised steel / brass, Sleeve I.D. 8, Operating pressure max. 16 bar, Temp. -20 °C to 100 °C

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates.

Specially designed for all applications susceptible to severe mechanical wear.

Strong, impact and vibration-resistant design for demanding environments.

The stream line type has an integrated hose stem.

### Tehnične Specifikacije

|                              |                                   |
|------------------------------|-----------------------------------|
| Min. sobna temperatura [°C]  | -20                               |
| Min. temperatura medija [°C] | -20                               |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar |
| Ohišje                       | Steel                             |
| Povezava                     | I.D. 8                            |
| Rokav                        | Hardened and nickel-plated steel  |
| Tesnilo                      | NBR                               |
| Vzmet                        | Stainless steel                   |
| DN                           | 7.6                               |
| Max. obratovalni tlak [bar]  | 16                                |
| Dolžina [mm]                 | 70.0                              |
| Max. sobna temperatura [°C]  | 100                               |
| Max. temperatura medija [°C] | 100                               |
| Pretok                       | 2100 l/min (air)                  |