

Datum: 01.05.2025



(slika je simbolična)

Hitre spojke I.D. 7.6, pocinkano /medenina, R 1/4 zunanji navoj

Kategorija: [Quick disconnect coupling DN 7.6, male](#)

Šifra: **107356RIE**

Kratek opis

Quick-connect coupling I.D. 7.6, galvanised steel / brass, R 1/4 ET, Operating pressure max. 16 bar, Temp. -20 °C to 100 °C

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates.

Specially designed for all applications susceptible to severe mechanical wear.

Strong, impact and vibration-resistant design for demanding environments.

The stream line type has an integrated hose stem.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Steel
Povezava	R 1/4 ET
Rokav	Hardened and nickel-plated steel
Tesnilo	NBR
Vzmet	Stainless steel
DN	7.6
Max. obratovalni tlak [bar]	16
a/f [mm]	20
Dolžina [mm]	63.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	2100 l/min (air)