

Datum: 01.05.2025



(slika je simbolična)

## Hitro oddušni ventil lineonline, z dušilko, G 1/8, za Ø 6 mm

Kategorija: [Quick-exhaust valve, with silencer, pipe-thread](#)

Šifra: **106778RIE**

### Kratek opis

Quick relief valve »lineonline«, with silencer, Hose - thread, G 1/8, for hose Ø 6 mm, Operating pressure 1 - 10 bar  
Exhaust can be silenced by a stainless steel silencer or conveyed using a push-in fitting with an air exhaust device.

### Tehnične Specifikacije

|                                     |                                                            |
|-------------------------------------|------------------------------------------------------------|
| Min. temperaturno območje [°C]      | -20                                                        |
| Navoj                               | G 1/8                                                      |
| Notranji deli                       | Nickel-plated brass, brass, technopolymer, stainless steel |
| Pnevmatski simboli                  | On housing                                                 |
| Telo                                | Technopolymer                                              |
| Tesnilo                             | NBR                                                        |
| Min. obratovalni tlak [bar]         | 1                                                          |
| Za cevi Ø [mm]                      | 6                                                          |
| Max. obratovalni tlak [bar]         | 10                                                         |
| I [mm]                              | 14.6                                                       |
| B [mm]                              | 25.5                                                       |
| A [mm]                              | 58.5                                                       |
| Max. temperaturno območje [°C]      | 60                                                         |
| Pretok pri 6,3 bara [NI/min]        | 270                                                        |
| Izhodni pretok pri 6,3 bar [NI/min] | 700                                                        |