

Datum: 11.05.2025



(slika je simbolična)

Javljal.kon.položaja ATEX tip SC-NS 2, induktiven NAMUR senzor

Kategorija: [End position feedback aluminium, ATEX](#)

Šifra: **103693RIE**

Kratek opis

End position feedback ATEX type SC-NS 2, inductive NAMUR sensors, 2-fold, Voltage range 8 V, Temp. -20 °C to 70 °C

Robust type in an aluminium housing

- Universal indicator for NAMUR sizes 80 x 30 and 130 x 30

- Height-adjustable feet that adapt to different pinion projections

- ON / OFF position indicator also visible from a distance

- Easy-to-adjust, self-locking trip cam

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Gred	Nickel-plated steel
IP zaščita	EX TDA21 IP66/67 T 85 °C
Izhodni tok	Damped <1 mA / undamped >3 mA
Kabelska uvodnica	M20x1.5, up to four cable glands possible
Ohišje	Die-cast aluminium EN AB 46100, epoxy powder-coated
Opis	End position feedback, with inductive NAMUR sensors, ATEX
Preklopna funkcija	Damped or undamped in the end position
Različica	with inductive NAMUR sensors, ATEX
Vijaki	Stainless steel
Območje napetosti	8 V
Max. temperaturno območje [°C]	70