

Datum: 11.05.2025



(slika je simbolična)

Kaljena spojka DN6, navoj 9 mm, blokirni ventil, konus 45°

Kategorija: [Temp. control coupling DN 6, with shut-off valve](#)

Šifra: **107912RIE**

Kratek opis

Tempered coupling DN 6, Taps 9 mm, Blocking valve, Brass, Hose sleeve 45°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C

Compatible with HASCO Z 8 system.

For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines.

Optionally with free passage, one or both sides sealing.

Female-threaded couplings and plugs with female-threaded PTFE seal.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
Priključek za cev [mm]	9
Max. obratovalni tlak [bar]	15
Dolžina [mm]	42.5
Tip stebelnih cevi	45°
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160