

Datum: 30.04.2025



(slika je simbolična)

## Kaljena spojka DN6, zunanji navoj, Medenina, M14x1.5 45°

Kategorija: [Temp. control coupl. DN 6, without shut-off valve](#)

Šifra: **107925RIE**

### Kratek opis

Tempered coupling DN 6, Exterior thread, Brass 2.0401, M14x1.5 45°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C

Compatible with HASCO Z 8 system.

For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines.

Optionally with free passage, one or both sides sealing.

Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

|                              |                         |
|------------------------------|-------------------------|
| Min. sobna temperatura [°C]  | -20                     |
| Min. temperatura medija [°C] | -20                     |
| Krogla                       | Stainless steel         |
| Material                     | Brass 2.0401            |
| Priključni navoj             | M14x1.5 45°             |
| Pritrdilni obroč             | Stainless steel         |
| Srednje                      | Air, water, oil, vacuum |
| Tesnilo                      | FPM (PTFE coated)       |
| Vzmet                        | Stainless steel         |
| Max. obratovalni tlak [bar]  | 15                      |
| a/f [mm]                     | 17                      |
| Dolžina [mm]                 | 47.0                    |
| Max. sobna temperatura [°C]  | 160                     |
| Max. temperatura medija [°C] | 160                     |