

Datum: 01.05.2025



(slika je simbolična)

## Kamlok Hitro spajane spojka z N.N.D tipAluminijG 1 1/2

Kategorija: [Kamlok female coupler, female threaded, Part D](#)

Šifra: **108045RIE**

### Kratek opis

Kamlok quick-connect socket with interior thread, D type, Aluminium, G 1 1/2, for plug Ø 53 mm, Pressure max. 16 bar, max. 68 °C

Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.

A male part and a female part are joined together by shifting the handles.

There is no need to turn the hose!

Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

All Kamlok quick coupling boxes and Kamlok closure boxes are supplied with NBR seal.

### Tehnične Specifikacije

|                                |                                    |
|--------------------------------|------------------------------------|
| Min. temperaturno območje [°C] | -20                                |
| Navoj                          | G 1 1/2                            |
| Tesnilo                        | NBR, resistant to oils and benzine |
| Max. obratovalni tlak [bar]    | 16                                 |
| Za vtič Ø [mm]                 | 53                                 |
| Max. temperaturno območje [°C] | 68                                 |
| C [mm]                         | 69.5                               |
| A [mm]                         | 87.4                               |