

Datum: 10.05.2025



(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 80hod 20G 1/8

Kategorija: [Compact cylinders double-acting, female piston rod](#)

Šifra: **106028RIE**

Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 80, Stroke 20, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 80°C

New series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	Aluminium
Batnica	C45 steel, hard chrome-plated
Batnica IT	M12
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	G 1/8
Serijska	LINER series
Standard	acc. to ISO 21287
Tesnilo	NBR
Min. nastavljeni tlak [bar]	0.4
Max. delovni tlak [bar]	10
Stroke [mm]	20
Bat Ø [mm]	80
Max. temperaturno območje [°C]	80