

Datum: 29.05.2025



(slika je simbolična)

Komp. cilind. del. v dveh smereh, batØ80, hod5, G1/8, ISO21287

Kategorija: [Compact cylinders double-acting, female piston rod](#)

Šifra: **155482RIE**

Kratek opis

Compact cyl.ISO 21287, double-acting, female piston rod, magnet, PistonØ80, Stroke5, G1/8, Work.press.max.10bar, Temp.-20°C to 70°C Series acc. to ISO 21287 characterised by a very short and compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M12x1.75
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	G 1/8
Serijska	ACE series
Standard	acc. to ISO 21287
Tesnilo	NBR
Stroke [mm]	5
Max. delovni tlak [bar]	10
Max. temperaturno območje [°C]	70
Bat Ø [mm]	80