

Datum: 30.04.2025



(slika je simbolična)

## Komp. cilind.del. v dveh smereh,bat Ø100,hod55,G1/8,ISO21287

Kategorija: [Compact cylinders double-acting, male piston rod](#)  
Šifra: **155766RIE**

### Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod  
magnet, PistonØ100, Stroke55, G1/8,  
Work.press.max.10bar, Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and  
compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed  
air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                |
|--------------------------------|--------------------------------|
| Min. temperaturno območje [°C] | -20                            |
| Bat                            | Aluminium                      |
| Batnica                        | S45C steel, hard chrome-plated |
| ET batnice                     | M16x1.5                        |
| Ffunkcija                      | double-acting                  |
| Gewinde Kolbenstange           | male piston rod                |
| Magnet                         | with magnet                    |
| Ovoj                           | Anodised aluminium             |
| Povezava                       | jacket with T-slots            |
| Serijska                       | G 1/8                          |
| Standard                       | ACE series                     |
| Tesnilo                        | acc. to ISO 21287              |
| Max. delovni tlak [bar]        | NBR                            |
| Stroke [mm]                    | 10                             |
| Max. temperaturno območje [°C] | 55                             |
| Bat Ø [mm]                     | 70                             |
|                                | 100                            |