

Datum: 01.05.2025



(slika je simbolična)

[Komp. cilind.del. v dveh smereh, bat Ø80, hod160, G1/8, ISO21287](#)

Kategorija: [Compact cylinders double-acting, male piston rod](#)
Šifra: **155749RIE**

Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod magnet, PistonØ80, Stroke160, G1/8, Work.press.max.10bar, Temp.-20°C to 70°C Series acc. to ISO 21287 characterised by a very short and compact design. The standard type features a magnetic piston. Piston rod optionally with male or female thread. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium S45C steel, hard chrome-plated
Batnica	M16x1.5
ET batnice	double-acting
Ffunkcija	male piston rod
Gewinde Kolbenstange	with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	G 1/8
Povezava	ACE series
Serija	acc. to ISO 21287
Standard	NBR
Tesnilo	10
Max. delovni tlak [bar]	70
Max. temperaturno območje [°C]	70
Bat Ø [mm]	80
Stroke [mm]	160