

Datum: 30.04.2025



(slika je
simbolična)

Komp. cilind.del. v dveh smereh,batØ125,hod100,G1/4,ISO21287

Kategorija: [Compact cylinders double-acting, male piston rod](#)

Šifra: **155800RIE**

Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod
magnet, PistonØ125,Stroke100, G1/4,
Work.press.max.10bar, Temp.-20°C to 70°C
Series acc. to ISO 21287 characterised by a very short and
compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed
air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome- plated
ET batnice	M20x1.5
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium
Povezava	jacket with T-slots
Serijska	G 1/4
Standard	ACE series
Tesnilo	acc. to ISO 21287
Max. delovni tlak [bar]	NBR
Max. temperaturno območje [°C]	10
Stroke [mm]	70
Bat Ø [mm]	100
	125