

Datum: 06.05.2025

(slika je  
simbolična)

## [komp.cilinder,enosmerni,zunanjibat Ø16, hod 5, M5, ISO21287](#)

Kategorija: [Compact cylinders, single-acting, extended, female](#)Šifra: **155908RIE**

### Kratek opis

Compact cyl.ISO 21287, single-acting, female piston rod, ext.,magnet,PistonØ16,Stroke5,M5, Work.press.max.10bar,Temp.-20°C to 70°C Series acc. to ISO 21287 characterised by a very short and compact design. The standard type features a magnetic piston. Piston rod optionally with male or female thread. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium S45C steel, hard chrome-plated
Batnica	M4x0.7
Batnica IT	single-acting
Ffunkcija	female piston rod with magnet
Gewinde Kolbenstange	Anodised aluminium jacket with T-slots
Magnet	M5
Ovoj	ATE series
Povezava	acc. to ISO 21287
Seriya	pressureless in the extended position
Standard	NBR
Starting position	5
Tesnilo	10
Stroke [mm]	16
Max. delovni tlak [bar]	70
Bat Ø [mm]	
Max. temperaturno območje [°C]	