

Datum: 06.05.2025



(slika je  
simbolična)

## **komp.cilinder,enosmerni,zunanjiP-Ø32, hod 10, G1/8, ISO21287**

Kategorija: [Compact cylinders, single-acting, extended, female](#)

Šifra: **155924RIE**

### Kratek opis

Compact cyl.ISO 21287,single-acting,female piston rod,  
ext.,magnet,PistonØ32,Stroke10,G1/8,Work.press.max.10ba  
r,Temp.-20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and  
compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed  
air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                   |                                          |
|-----------------------------------|------------------------------------------|
| Min. temperaturno<br>območje [°C] | -20                                      |
| Bat                               | Aluminium                                |
| Batnica                           | S45C steel, hard chrome-<br>plated       |
| Batnica IT                        | M8x1.25                                  |
| Ffunkcija                         | single-acting                            |
| Gewinde Kolbenstange              | female piston rod                        |
| Magnet                            | with magnet                              |
| Ovoj                              | Anodised aluminium                       |
| Povezava                          | jacket with T-slots                      |
| Serijska                          | G 1/8                                    |
| Standard                          | ATE series                               |
| Starting position                 | acc. to ISO 21287                        |
| Tesnilo                           | pressureless in the<br>extended position |
| Max. delovni tlak [bar]           | NBR                                      |
| Stroke [mm]                       | 10                                       |
| Bat Ø [mm]                        | 10                                       |
| Max. temperaturno<br>območje [°C] | 32                                       |
|                                   | 70                                       |