

Datum: 06.05.2025



(slika je  
simbolična)

## [komp.cilinder,enosmerni,zunanjiP-Ø 32, hod 5, G1/8, ISO21287](#)

Kategorija: [Compact cylinders, single-acting, extended, female](#)

Šifra: **155923RIE**

### Kratek opis

Compact cyl.ISO 21287, single-acting,female piston rod,  
ext.,magnet,PistonØ32,Stroke5,G1/8,Work.press.max.10bar,  
Temp.-20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and  
compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed  
air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                   |                                           |
|-----------------------------------|-------------------------------------------|
| Min. temperaturno<br>območje [°C] | -20                                       |
| Bat                               | Aluminium                                 |
| Batnica                           | S45C steel, hard chrome-<br>plated        |
| Batnica IT                        | M8x1.25                                   |
| Ffunkcija                         | single-acting                             |
| Gewinde Kolbenstange              | female piston rod                         |
| Magnet                            | with magnet                               |
| Ovoj                              | Anodised aluminium<br>jacket with T-slots |
| Povezava                          | G 1/8                                     |
| Serijska                          | ATE series                                |
| Standard                          | acc. to ISO 21287                         |
| Starting position                 | pressureless in the<br>extended position  |
| Tesnilo                           | NBR                                       |
| Stroke [mm]                       | 5                                         |
| Max. delovni tlak [bar]           | 10                                        |
| Bat Ø [mm]                        | 32                                        |
| Max. temperaturno<br>območje [°C] | 70                                        |