

Datum: 30.04.2025



(slika je simbolična)

## Kompaktni cilindri, enosmerni, bat Ø 20, hod 15,M5,ISO21287

Kategorija: [Compact cylinders single-acting, retracted, female](#)

Šifra: **155821RIE**

### Kratek opis

Compact cyl.ISO 21287, single-acting, female piston rod, retr., magnet, Piston Ø20, Stroke 15, M5, Work.press.max.10 bar, Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                        |
|--------------------------------|----------------------------------------|
| Min. temperaturno območje [°C] | -20                                    |
| Bat                            | Aluminium                              |
| Batnica                        | S45C steel, hard chrome-plated         |
| Batnica IT                     | M6x1.0                                 |
| Ffunkcija                      | single-acting                          |
| Gewinde Kolbenstange           | female piston rod                      |
| Magnet                         | with magnet                            |
| Ovoj                           | Anodised aluminium jacket with T-slots |
| Povezava                       | M5                                     |
| Serijska                       | ASE series                             |
| Standard                       | acc. to ISO 21287                      |
| Starting position              | pressureless in the retracted position |
| Tesnilo                        | NBR                                    |
| Max. delovni tlak [bar]        | 10                                     |
| Stroke [mm]                    | 15                                     |
| Bat Ø [mm]                     | 20                                     |
| Max. temperaturno območje [°C] | 70                                     |