

Datum: 30.04.2025



(slika je simbolična)

Kompaktni cilindri, enosmerni, P-Ø 32, hod 25, G1/8, ISO 21287

Kategorija: [Compact cylinders single-acting, retracted, female](#)

Šifra: **155833RIE**

Kratek opis

Compact cyl. ISO 21287, single-acting, female piston rod, retr., magnet, Piston Ø32, Stroke 25, G1/8, Work. press. max. 10 bar, Temp. -20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M8x1.25
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Anodised aluminium
Povezava	jacket with T-slots
Serijska	G 1/8
Standard	ASE series
Starting position	acc. to ISO 21287
Tesnilo	pressureless in the retracted position
Max. delovni tlak [bar]	NBR
Stroke [mm]	10
Bat Ø [mm]	25
Max. temperaturno območje [°C]	32
	70