

Datum: 12.05.2025



(slika je simbolična)

Kompaktni cilinder, enosmerni, P-Ø 40, hod 5, G1/8,ISO21287

Kategorija: [Compact cylinders single-acting, retracted, female](#)
Šifra: **155834RIE**

Kratek opis

Compact cyl.ISO 21287, single-acting,female piston rod,retr.,magnet,PistonØ40,Stroke5,G1/8,Work.press.max.1 0bar,Temp.-20°C to 70°C
Series acc. to ISO 21287 characterised by a very short and compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M8x1.25
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	G 1/8
Povezava	ASE series
Serijska	acc. to ISO 21287
Standard	pressureless in the retracted position
Starting position	NBR
Tesnilo	5
Stroke [mm]	10
Max. delovni tlak [bar]	40
Bat Ø [mm]	70
Max. temperaturno območje [°C]	