

Datum: 01.05.2025



(slika je simbolična)

## **Kompaktni cilindri, enosmerni, P-Ø100, hod 15, G1/8, ISO21287**

Kategorija: [Compact cylinders, single-acting, retracted, male](#)Šifra: **155903RIE**

### **Kratek opis**

Compact cyl.ISO 21287, single-acting, male piston rod, retr., magnet, Piston Ø100, Stroke 15, G1/8, Work.press.max .10bar, Temp. -20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### **Tehnične Specifikacije**

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M16x1.5
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	G 1/8
Serijska	ASE series
Standard	acc. to ISO 21287
Starting position	pressureless in the retracted position
Tesnilo	NBR
Max. delovni tlak [bar]	10
Stroke [mm]	15
Max. temperaturno območje [°C]	70
Bat Ø [mm]	100