

Datum: 08.05.2025



(slika je simbolična)

## Kontrolni ventil, lahka izvedba, nerjavno jeklo, G 2 1/2

Kategorija: [Check valve straight-way type, lightweight series](#)

Šifra: **103857RIE**

### Kratek opis

Check valve, Lightweight construction, Stainless steel  
1.4301, Operating temperature -20 °C to 150 °C, G 2 1/2, PN  
max. 16 bar  
Stainless steel check valve with full bore and very low  
opening pressure, no maintenance required.  
Applications: Compressed air, water, neutral gases, gaseous  
and liquid non-corrosive media, oils.

### Tehnične Specifikacije

|                               |                           |
|-------------------------------|---------------------------|
| Min. delovna temperatura [°C] | -20                       |
| Navoj                         | G 2 1/2                   |
| Ohišje                        | Stainless steel<br>1.4301 |
| Tesnilo                       | FKM                       |
| Vzmet                         | Stainless steel<br>1.4301 |
| Min. tlak odpiranja [bar]     | 0.03                      |
| Max. obratovalni tlak [bar]   | 16                        |
| A [mm]                        | 80.0                      |
| C [mm]                        | 113.0                     |
| L [mm]                        | 141.5                     |
| Max. delovna temperatura [°C] | 150                       |