

Datum: 30.04.2025



(slika je simbolična)

## Kontrolni ventil nagnjen sedež nerjavno jeklo, G 2, 0.2 bar

Kategorija: [Unidirectional valves angle-seat, stainless steel](#)

Šifra: **103839RIE**

### Kratek opis

Check valve inclined seat design stainless steel,  
Medium/ambient temp. -10°C to 230°C, G 2, max. 40 bar,  
Opening pressure 0.2 bar

### Tehnične Specifikacije

|                               |                                      |
|-------------------------------|--------------------------------------|
| Min. delovna temperatura [°C] | -10                                  |
| Min. sobna temperatura [°C]   | -10                                  |
| Min. temperatura medija [°C]  | -10                                  |
| Navoj                         | G 2                                  |
| Notranji deli                 | Stainless steel<br>1.4401 / 1.4408   |
| Ohišje                        | Stainless steel<br>1.4401 / 1.4408   |
| Standardni navoj              | G thread acc. to DIN<br>EN ISO 228-1 |
| Tesnilo                       | FKM                                  |
| Min. tlak odpiranja [bar]     | 0.2                                  |
| Max. obratovalni tlak [bar]   | 40                                   |
| a/f [mm]                      | 70                                   |
| B [mm]                        | 131.0                                |
| L [mm]                        | 151.0                                |
| Max. delovna temperatura [°C] | 230                                  |
| Max. sobna temperatura [°C]   | 230                                  |
| Max. temperatura medija [°C]  | 230                                  |