

Datum: 30.04.2025



(slika je simbolična)

[krog. ventil fina nastavitvev, nikljana lahka med., 1 1/2](#)

Kategorija: [Potable water ball valves with fine adjustment](#)Šifra: **138877RIE**

Kratek opis

Ball valve fine adjustment, Potable water, nickel-plated bright brass, Temp. -15°C to 120°C, Rp 1 1/2, DN 40, PN max 40 bar

Brass ball valves in the standard series with fine adjustment.

Unlike our classic standard ball valves (open-close function), this model features a special stem technology that allows finely modulated opening and closing of the line.

The flow rate can be regulated extremely precisely as a result.

The cock is made of low-lead brass with a bare brass surface on the inside. It is thus safe to use with drinking water. This valve complies with the European standard EN 13828 and the working paper DVGW W 570.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-15
DVGW odobritev	DIN EN 13828:2003-12, DVGW W 570
Kolo	Plastic
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Brass with a bare metal surface
Navoj	Rp 1 1/2
Ohišje	Nickel-plated brass (outside), brass with a bare metal surface (inside)
Standardni navoj	Thread acc. to ISO 7/1
Stebelno tesnilo	PTFE / NBR
DN	40
PN [bar]	40
L [mm]	106.4
B [mm]	119.0
Max. delovna temperatura [°C]	120
A [mm]	129.6