

Datum: 30.04.2025

**[krog. ventil med., pnevm. vklop enojno delovanje, Rp 3/4](#)**

(slika je simbolična)

Kategorija: [Brass ball valve, single-acting actuator](#)Šifra: **158748RIE****Kratek opis**

Brass ball valve, Pneumat. actuation drive, NAMUR, single-acting, Operating temp. -20 °C to 150 °C, Rp 3/4, DN 20, PN max. 16 bar

Ball valves with pneumatic actuator.

Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Tehnične Specifikacije

Min. delovna temperatura aktuatorja [°C]	-20
Min. delovni tlak krogelnega ventila [°C]	-20
Adapter ventila	Integrated to NAMUR Nickel-plated brass, with flange plate ISO 5211
Material krogelnega ventila	Rp 3/4
Navoj	Anodised aluminium
Pogonski material	PTFE / FKM
Premaz za krogelni ventil	NBR
Premaz za pogon	single-acting - spring to close
Različica	
Priporočeni vodeni tlak [bar]	5.6
Max. vodeni tlak aktuatorja [bar]	8.4
Max. delovni tlak krogelnega ventila [bar]	16
DN	20
L [mm]	77.0
Max. delovna temperatura aktuatorja [°C]	80
Kot vrtenja [°]	90
B [mm]	115.8
Max. delovni tlak krogelnega ventila [°C]	150
A [mm]	233.2